

Product News



New Honda V-Twin General-Purpose Engine

Honda introduces the all-new generation of its popular and durable V-Twin general purpose engine. Featuring six all new models, the new V-Twin engine line offers customers more power, versatility, and greater fuel economy in a more compact package. The new GX630, GX660, GX690, GXV630, GXV660, and GXV690 engines are available in both horizontal and vertical shaft configurations for a greater range of utility covering a wide range of demanding commercial, rental, and turf applications.

Circle 801

Note: Product News submissions should be emailed to chuckp@adpub.com or mailed to Product News, 1000 Nix Rd., Little Rock, AR 72211. Please be sure that your product announcement is accompanied by a photo of the product. cr

CAT Announces New Triplex Positive Displacement Plunger Pump

The new 10,000 psi Model 1810 has been added to our line. This pump delivers a low pulsation flow of 3 gpm @ 10,000 psi. It has a low unswept volume [minimal un-evacuated liquid remains in the pumping chamber] resulting in maximum volumetric efficiency. It has a compact footprint for portable and stationary installation. Custom features include: block-style manifold of heat-treated 304 stainless steel, high-strength plunger rods, oversized bearings and chrome-moly crankshaft, 304 stainless steel seat mates with a ceramic ball to provide true sphericity, solid ceramic plungers, custom delrin seals and UHMV V-packings. Optional 15,000 psi rupture disc, regulating relief valve, and pressure gauge. Each pump can be fitted with optional adapters for standard NPT connection.

Circle 804



Hotsy Introduces NESTechnology in High-Pressure Pump

Hotsy introduces the latest innovation, NESTechnology. It stands for Nested Seal Technology, where the pump actually "nests" the seals of the pump's high-pressure packing assembly in place, supporting the side walls. The technology includes new high and low-pressure u-shaped seals surrounded by thicker brass pressure rings. This provides better wall support while withstanding higher water temperatures. Other features of the new Hotsy high-pressure pump include: Extended time between seal replacement, Teflon bronze rings support the U-Seal, The low-pressure U-Seal has a unique double lip to provide for greater suction and less chance of water leakage. The nesting assembly is stronger and holds up better to spikes in water pressure.

Circle 802



Pressure-Pro Introduces New Line of 4-Wheel Portable Electric Direct Drive Hot Water Washers

The line offers flow rates from 3.0 gpm to 4.0 gpm and pressure ranges of 2000 psi to 4000 psi. All models feature a rugged 1¼-in. powder-coated steel roll cage frame with lifting hook, ¾-in. cold rolled steel axles, pneumatic tires with steel rims, super efficient schedule 80 coil with 1-piece rigid insulation combustion chamber, stainless steel coil wrap, 9-gallon poly diesel tank with fuel filter, high limit over temp protection, safety pressure relief valve, and thermo sensor to prevent overheating in bypass mode. All models are powered by Beckett burners, Marathon commercial industrial grade electric motors, and feature AR, CAT, and GP direct-drive pumps.

Circle 803

